## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization International Bureau



### | 10011 | 1111707 | 1 21117 | 1111 | 1111 | 1111 | 1111 | 1111 | 1111 | 1111 | 1111 | 1111 | 1111 | 1111 | 111

(43) International Publication Date 5 February 2004 (05.02.2004)

PCT

# (10) International Publication Number WO 2004/011547 A1

(51) International Patent Classification7: 23/04, B65D 1/00

C08L 23/06.

(21) International Application Number:

PCT/EP2003/007941

(22) International Filing Date:

18 July 2003 (18.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 02078183.7

25 July 2002 (25.07.2002) EP

- (71) Applicant (for all designated States except US): SOLVAY POLYOLEFINS EUROPE-BELGIUM (S.A.) [BE/BE]; Rue du Prince Albert, 44, B-1050 Brussels (BE). –
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): GORGERIN, Michel, Oswald [BE/BE]; Rue D'Ecaussinnes, 2, B-7062 Soignies (BE).
- (74) Agent: SMITH, Julian, Philip, Howard; BP International Limited, Patents and Agreements, Chertsey Road, Sunbury on Thames, Middlesex TW16 7LN (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,

SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, Fl, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, Cl, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Declarations under Rule 4.17:

- as 10 applicant's entitlement 10 apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- of inventorship (Rule 4.17(iv)) for US only

### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONTAINER FORMED FROM MULTIMODAL ETHYLENE POLYMER

(57) Abstract: A container is disclosed comprising a multimodal ethylene polymer having a standard density of at least 950 kg/m<sup>3</sup> and a fluidity index MI<sub>2</sub> of from 1 to 10 g/10 min, said multimodal ethylene polymer comprising: from 20 to 65 wt%, based on the total weight of the multimodal ethylene polymer, of a fraction comprising ethylene polymer (A) having a density of more than 965 kg/m<sup>3</sup> and a fluidity index MI<sub>2</sub>(A) of at least 10 g/10 min; and from 80 to 35 wt %, based on the total weight of the multimodal ethylene polymer, of a fraction comprising a copolymer (B) of ethylene and at least one alpha-olefin containing from 3 to 12 carbon atoms, and having a fluidity index MI<sub>2</sub>(B) of less than 10 g/min and a content of said alpha-olefin(s) of 0.1 to 5 mol%.